

Masini actionate hidraulic



Pompe submersibile Mașini portabile de tăiat rosturi Mașini de carotat Sfredel

	HWP 2	HWP 3	HCS 14	HCS 16	HSC 18	HCD 50-200	HCD 25-100	HED
Presiune maxima - bar	172	172	172	172	172	170	170	210
Debit de ulei – l/min	20	20-30	20-30	20-30	20-34	20	20	20-40
Adancime maxima de taiere – mm	-	-	137	162	187	-	-	-
Diametru disc – mm	-	-	350	400	450	-	-	-
Greutate – kg	7,7	11	9,7	10,5	11,2	8,2	8,2	19,6
Diametru de gaurire – mm	-	-	-	-	-	Ø 50 ÷ 200	Ø 25 ÷ 100	Ø 250
Turatie – rot/min	-	-	-	-	-	600	1.500	-
Prindere carote	-	-	-	-	-	1 ¼ UNC	1 ¼ UNC	-
Sfredel	-	-	-	-	-	-	-	(Ø 90÷350) x 700
Racord – mm	50	75	-	-	-	-	-	-
Diametrul particulelor aspirate – mm	38	62	-	-	-	-	-	-
Debit maxim – l/mm	670	1330	-	-	-	-	-	-

Ciocane demolatoare actionate hidraulic



*Cu exceptia HH 10 maner D si HRD 20 toate ciocanele demolatoare au amortizor de vibratii

	HH 10 maner D	HH 23 maner T	HH 23 maner T	HH 23 maner T	HH 25 maner T	HH 25 maner T	HH 27 maner T	HRD 20 rock drill max Ø 45 mm
Presiune maxima - bar	160	160	160	160	160	160	160	160
Debit de ulei – l/min	20	20	20	30	20	30	30	20-25
Energie de lovire - J	22	60	85	95	85	95	105	60
Percutie – batai/min	1600	1560	1380	1380	1380	1380	1260	1560
Dimensiuni scula – mm	S 19x50	S 25x108	S 25x108	S 25x108	S 32x160	S 32x160	S 32x160	S 22x108
Greutate – kg	10	22	23	23	25	25	27	20